

LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

Section 1 • Product and Company Identification

LPS® Food Grade Machine Oil **Product Name:**

01316, C01316 **Part Number:**

Chemical Name: Petroleum Distillates mixture

Product Use: A spray lubricant designed to displace moisture from mechanical and electrical equipment.

provide light-duty lubrication in food processing applications.

Manufacturer Information: LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA, USA 30084

TEL: 1 770-243-8880

Emergency Telephone

1-800-424-9300 Chemtrec; Number: Outside U.S.: (703) 527-3887

FAX: 1 770-243-8899

Website: http://www.lpslabs.com

PLAIN LANGUAGE HAZARD SUMMARY

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably won't help the non-professional. LPS includes this "PLAIN LANGUAGE HAZARD SUMMARY" to address the questions and concerns of the average worker. If you have additional health, safety or product questions, don't hesitate to call us at 800/241-8334.

Worker Toxicity

LPS® Food Grade Machine Oil is an industrial lubricant. It contains petroleum distillates and mineral oil, which can be irritating to skin. We suggest you wear gloves and avoid extended exposure to unprotected skin. Don't get it in your eyes (it stings), or breath large amounts of the vapor, (it may irritate the respiratory tract). Don't spray large amounts of LPS Food Grade Machine Oil for extended periods without adequate ventilation. If you're going to perform work involving a lot of product in a poorly ventilated area, use of a respirator may be necessary. For more exposure and first aid information, refer to MSDS Sections 2, 8 and 11.

Flammability

LPS® Food Grade Machine Oil is flammable. However, Under normal use conditions flammability isn't a concern, but don't apply the product onto red-hot metal surfaces or near sparks. For additional information on flammability refer to sections 5, 9, and 16.

Disposal

If you spill LPS® Food Grade Machine Oil, notify the proper environmental or safety department. Waste must be disposed of in accordance with national, regional, provincial and local environmental control regulations. See section 13 for more details.



LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

Section 2 • Hazards Identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Emergency Overview: DANGER: Flammable. Contents under pressure. Harmful or Fatal if Swallowed.

Primary route(s) of entry: Skin and Eye contact. Inhalation.

Potential Acute Health Effects:

Eyes: Irritating to eyes.

Skin: Repeated exposure may cause skin dryness or cracking.

Inhalation: Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or

headache.

Ingestion: Product has a low order of acute oral toxicity, but ingestion of large quantities may cause

nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No IARC: No OSHA: No

Mutagenic Effects: None known.

Teratogenic Effects: None known.

Target Organ Effects: None known.

Medical conditions aggravated by exposure:

Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

Signs and Symptoms:

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

Section 3 – Composition / Information on Ingredients

Components	CASRN	Weight Percent
Aliphatic Hydrocarbon	64742-47-8	50-60%
White Mineral Oil	8042-47-5	25-50%
Carbon Dioxide	124-38-9	1-5%



LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

Section 4 - First Aid Measures

Eyes: Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low

pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and

eyelid tissue. Do not use eye ointment. Seek medical attention immediately.

Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do

not use ointments. Seek medical attention if irritation persists.

Inhalation: Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If

heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek

medical attention immediately.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth

to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended.

Seek medical attention immediately.

Section 5 – Fire Fighting Measures

Products of Combustion: Carbon monoxide and carbon dioxide.

Firefighting media: Use CO2, dry chemical powder, water spray, fog or foam. Cool containing vessels with water jet

in order to prevent pressure build-up, auto ignition or explosions.

Sensitivity to Impact: None. Sensitivity to Static Discharge: None.

Protection Clothing (Fire): wear protective clothing and equipment suitable for the surrounding fire, including helmet, face mask, and self-contained breathing apparatus.

Special Remarks on Explosion Hazards: High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers. Aerosols may explode upon heating, spread fire and overcome sprinkler systems.

Section 6 – Accidental Release Measures

Containment Small Spill and Leak: Absorb with an inert material and dispose of properly. **Procedures** Large Spill and Leak: Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal. Clean-Up Recover free product and place in suitable container for disposal. Do not allow to enter drains, **Procedures** sewers or waterways. Spillages or uncontrolled discharges into waterways must be alerted to the Environment Agency or other appropriate regulatory body. **Evacuation** Ventilate area of leak or spill. Keep unnecessary and unprotected people away. **Procedures** Special Remove all sources of ignition. Ventilate area. Wear appropriate protective equipment during **Procedures** cleanup.



LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

Section 7 - Handling and Storage

Handling: DO NOT spray into or around ignition sources. Do not allow material to come into contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Do not breathe vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

Storage: Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

Precautions to be taken in handling and storage: *Store aerosols as Level 3 Aerosol (NFPA 30B).* Store all materials in dry, well-ventilated area. Avoid breathing vapors.

Section 8 – Exposure Controls / Personal Protection

Exposure Guidelines:

Component	CASRN	OSHA TWA-PEL	OSHA STEL	ACGIH-TLV	ACGIH-STEL	NIOSH REL
Aliphatic Hydrocarbon	64742-47-8	100 ppm* 525 mg/m ³ *	Not Established	Not Established	Not Established	Not Established
White Mineral Oil	8042-47-5	5 mg/m ³ Oil Mist	Not Established	5 mg/m ³ Oil Mist	10 mg/m ³ Oil Mist	Not Established
Carbon Dioxide	124-38-9	5000 ppm	30000 ppm	5000 ppm	30000 ppm	5000 ppm TWA 30000 ppm STEL

Supplier recommendation

Engineering measures

Provide general and/or local exhaust ventilation to keep exposures below the exposure

guidelines listed above.

Personal protective equipment

Eye protection Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and

emergency shower facilities are recommended.

Hand protection Normally no hand protection is required; however, if product will be sprayed for an extended

period, "overspray" onto skin may occur. If so, use chemical resistant gloves (i.e., nitrile, neoprene, buna) conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.

Respiratory protection

Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits use NIOSH

approved respiratory protection.



LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

Section 9 – Physical and Chemical Properties

Appearance: Clear liquid. Color: Pale, Amber

Odor/Taste: Wintergreen, Petroleum Evaporation Rate: <0.1 BuAc=1

Solubility Description: Not Soluble in water Flash Point (°C): >70°C(174°F)

Odour Threshold: Not Determined. Flash Point Method: Tag-Closed Cup.

Boiling Point: > 224°C(435°F) Decomposition Temperature: Not Determined.

Specific Gravity (Water=1): 0.81-0.83 Auto Ignition Temperature : >228°C(490°F)

Vapour Density (Air=1): 4.7 Partition Coefficient <1

(octanol/water):

Vapor Pressure @ 20 °C: < 0.05 mmHg **Volatiles:** 60%

pH: Not applicable V.O.C. content 0%, 0 g/L, 0#/gal

Per CARB/EPA/OTC

definition
Viscosity: 130 - 160 cPs

Flammable limits LOWER: 0.6% (estimated): UPPER: 7%

Melting Point (°C): Not Applicable

Section 10 - Chemical Stability and Reactivity

Chemical Stability: Product is stable under recommended storage conditions.

Conditions to Avoid: Keep away from heat and ignition sources.

Incompatibility: Extremely reactive or incompatible with oxidizing agents.

Hazardous Combustion will generate smoke, possibly thick and choking, resulting in zero visibility and

Decomposition: combustion products include oxides of sulfur, chlorine, carbon monoxide and carbon dioxide.

Hazardous Will not occur.

Polymerization:



LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

Section 11 - Toxicological Information

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

B: Component Analysis

Component	CASRN	LC-50	LD-50
Aliphatic Hydrocarbon	64742-47-8	>6.8 mg/L (Supplier Data)	>5 g/kg (Supplier Data)
White Mineral Oil	8042-47-5	Not established	Not established
Carbon Dioxide	124-38-9	Not established	Not applicable

Section 12 - Ecological Information

Mobility: Semi-volatile. Readily absorbed

into soil.

Persistence and degradability:

Only slightly biodegradable.

Bioaccumulative potential:

No bioaccumulation potential

Other adverse effects:

None known.

Ecotoxicology

Effect on Organisms	Component	nt CASRN Test		Species	Results	
Acute Toxicity on Fishes	Aliphatic Hydrocarbon	64742-47-8	96-hr LC ₅₀	Oncorhynchus mykiss	3200 ug/L	
Acute Toxicity on Daphnia						
Bacterial inhibition						
Growth inhibition of algae	No Data Available					
Bioaccumulation in fish						

For the 64742-47-8 component, no toxicity has been observed in water due to extremely low water solubility. If material is spilled on soil, some potential toxic effects could occur before biodegradation could remove material.

Section 13 – Disposal Considerations

Waste Status: Aerosol products, if depressurized and emptied to less than 2.5 cm of fluid contents are classified as

non-hazardous waste under 40 CFR 261.7 (U.S.). If disposed of in its received form, this item carries

waste code D003. (U.S.)

Disposal: Waste must be disposed of in accordance with national, regional, provincial, and local environmental

control regulations.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste

management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and

local waste disposal requirements may be more restrictive than federal laws and regulations.



LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

Section 14 – Transportation Information

	Shipping Name:	Consumer Commodity	UN Number:	NA	
D.O.T. Ground	Hazard Class:	ORM-D	Technical Name:	NA	
	Subclass: NA Haza		Hazard Label:	ORM-D Already on box	
	UN no:	1950	ADR Class:	2	
Road/Rail -	Packing group:	NA	Classification code:	5F	
ADR/RID	Name and Description:	AEROSOLS, Flammable	Hazard ID no:	NA	
	Labeling:	2.1			
	UN no:	1950	Class:	2.1	
IMDG-IMO	Shipping Name:	AEROSOLS	Subsidiary Risk:	2.1	
	Packing Instructions:	P003, LP02	Packing group:	NA	
	Marine pollutant:	NO	EmS:	F-D, S-U	
	UN no:	1950	Class:	2.1	
IATA-ICAO	Shipping Name:	AEROSOLS, Flammable	Subclass	NA	
	Packing instructions:	203, Y203 (Ltd. Qty.)	Packing group:	NA	
	Labeling:	Flammable Gas			

Section 15 – Regulatory Information

U.S. Federal Regulations

RCRA Hazardous Waste No.: D003 (aerosols only)

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): None

Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title III SARA Section 311/312 (40 CFR 370) Hazard Categories:

Sudden Release of Pressure (aerosols only), Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): No individual section 313 component is present at or above 1%

Section 112 Hazardous Air Pollutants (HAPs): None



LPS® Food Grade Machine Oil

Revision Date: 6/08/10 Supercedes: 8/27/09

State Regulations

California: This product does <u>not contain chemical(s)</u> known to the State of California to cause cancer, birth defects or reproductive harm.

New Jersey Right to Know:

Aliphatic Hydrocarbon 64742-47-8 • White Mineral Oil 8042-47-8 • Carbon Dioxide 124-38-9

International Regulations

Canadian Environmental Protection Act: All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System WHMIS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification:

WHMIS Classification: Aerosol Class A, Class B5, Class D2B







Other Regulations

Montreal Protocol listed ingredients: None. Stockholm Convention listed ingredients: None. Rotterdam Convention listed ingredients: None. None. RoHS Compliant: Yes.

Section 16 • Other Information

	HMIS 1996		HMIS III		NFPA	
MSDS# 11316 Responsible Name:	Health:	1	Health:	[/]1	Flammability	
Clea George Regulatory Affairs Coordinator	Flammability:	2	Flammability:	3	Health 1 0 Reactivity	
	Reactivity	0	Physical Hazard:	0		

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Clea George, Regulatory Affairs Coordinator LPS Laboratories, A division of Illinois Tool Works